



技术要求

- 1、起重机的设计、制造、安装、试验、检验应符合 GB/T14406-93《通用门式起重机》的规定。
- 2、起重机大车缓冲器碰头安装由用户自行完成，其位置要保证大车运行机构断电后起重机滑行距离大于左表中数值。
- 3、起重机吨位牌的大小、式样及安装由各厂自定。
- 4、导电方式由需方自定。

10~50/10t 双梁J型吊钩门式起重机

- | | | |
|---------------|----------|--------|
| 1、大车导电架, 电缆卷筒 | 2、门架 | 3、电气部分 |
| 4、小车 | 5、大车运行机构 | |

起重量 Cap	跨度 Span	尺寸 Dimensions(mm)													
		Lx	BQ	Bx	B	H	H1	H2	H3	H4	L1	L2	S1	S2	
10	18	7000	9150	2100	11240	14438	12000	11500		9400	8750	8750	6500	6500	
	22					14488	12050								
	26					12528	14738								12300
	30					11990	14688								12250
16	18	7000	9500	2600	10820	14555	12000	10500		8400	8000	8000	5500	5500	
	22					14655	12100								
	26					11980	15810	13250	12000	11000	9500	9500	7500	7500	
20/10	18	7000	9500	2600	11550	14555	12000	11000	10500	9400	8000	8000	5500	5500	
	22					14655	12100								
	26		8500		11990	14547	12000				9500	9500	7500	7500	
	30					11748	15181								12622
	35				15359		12800								
30/10	22	7000	8500	2600	11748	16003	13200	12000	11500	10000	9500	9500	7000	7000	
	26														
36/16	26	7000	8500	2600	11042	16270	13300	12000	11500	11000	10500	10500	7500	7500	
	30														
50/10	32	7000	8500	3100	12918		14200	13000	12000	11260	14000	14000	11000	11000	

起重量(Cap)		t	10					16			20/10					30/10		36/16		50/10	
跨度 (Span)		m	18	22	26	30	35	18	22	30	18	22	26	30	35	22	26	26	30	32	
工作制 Duty			中 纜 Medium					中 纜 Medium			中 纜 Medium					中 纜 Medium		重 纜 Heavy		中/重 纜 Heavy/Medium	
起升高度 Lifting Height		主 Main 副 Aux	m	11.5					10.5		12	10.5					10.5		11.5	12	
												11					12		12	13	
速度 Speed	起升 Hoisting	主 Main 副 Aux	m/min	18.4					12.3			9.2					10.4		10.4	6	
												18.4					18.4		12.3	18	
	小车运行 Traveling		43.8					44.5			44					41.9		53	38.13		
	大车运行 Traveling		54.6		51.2	48.4		51.2	49.1		51					51.2		51.1	43.8		
电动机 Motor	起升 Hoisting	主 Main 副 Aux	型号/ 功率	YZR225M-8/26Kw					YZR250M1-8/30Kw			YZR250M1-8/35Kw					YZR315S-10/63Kw	YZR315S-10/63Kw	YZR315S-10/63Kw		
												YZR250M1-8/35Kw					YZR250M1-8/35Kw	YZR250M1-8/35Kw	YZR250M1-8/30Kw		
	小车运行 Traveling		YZR132M1-6/2.5Kw					YZR132M2-6/3.7Kw			YZR132M2-6/4Kw					YZR132M2-6/4	YZR160M2-6/6.3Kw	YZR160M2-6/5.5Kw			
	大车运行 Traveling		YZR132M1-6 2.5X4		YZR160M1-6 4X4	YZR160M2-6 8.5X4		YZR160M2-6 8.5X4		YZR160L-6 11X4	YZR160L-6 11X4					YZR160L-6 11X4		YZR160L-6 11X4			
总重 Total weight			t	63.2	67.2	84	100.5	135	75.5	83.3	105.5	79	88.5	99	110	132	125.4	130	142	148	204
最大轮压 Max wheel loading				23	24	30	36	40	36.4	40.5	23	30	31	35	39	42	35	36	38	39	48
卷筒轴 Crane Rail Recommended			P43					P50			P50 QU70					P50		P50		P50	
电源 Power supply			三相交流电 50Hz 380V																		