



Electric wire rope hoists MT type Conveying one with two trolleys, reeving 4/1

(1) with micro-lifting

Type	Reeving 4/1		Dimensions, mm																													
	Lifting height, m	Lifting capacity, kg	Lifting speed m/min		L2	L3	L4	L5	L6	L7	L8	L9	H1	H2	H3	H4	B	B1	B2	B3	B4	B5	B6	B7	C	e	D					
			4	6																								4/1	6/1			
			L1																													
MT305	H4	10	2000	1114	1154	512	629	202	-58	1044	225	415	70	317	195	148	33	90...	630	230	239.5	245...	94...	45	165	1080	22.5	120				
	H5	13.5		1314	1354	612	829	302	-108	1244								110				305	54						198 ⁽¹⁾			
MT410	H4	10	4000	1226	1290	567	641	183	-41	1177	280	536	80	380	235	200	37	130...	686	254	250	270...	125..	50	172	1265	8	175				
	H5	13		1426	1490	667	841	283	-91	1377								150				335	105						220 ⁽¹⁾			
MT516	H4	9	6300	1306	1373	602	711	202	-42	1247	280	536	80	380	235	200	37	130...	686	254	250	270...	125..	56	172	1340	7.5	175				
	H5	12.5		1526	1593	712	931	312	-97	1467								150				335	105						226 ⁽¹⁾			
MT625	H3	5.5	10000	1115	1203	500	611	62	29	1206	310	595	90	466	297	230	30	130...	836	310	294	300...	145..	71	212	1645	15	210				
	H4	8.5		1325	1413	605	663	130	13	1258																			292	150	125	257 ⁽¹⁾
	H5	11.5		1535	1623	710	873	236	-40	1468																			300...	145..	1640	
	H6	15		1815	1903	850	1153	378	-120	1748																			365	125		
	H7	17.5		1955	2043	920	1293	588	-285	1888																			365	125		
	H8	20		2125	2213	1005	1463	673	-328	2058																			365	125		
MT732	H4	8.5	12500	1453	1488	667	713	117	36	1308	310	595	100	540	292	230	30	130...	978	369	373	300...	145...	90	266	1905	22.5	210				
	H5	11.5		1668	1703	775	928	224	-18	1523																			150	125		
	H6	14.5		1883	1918	882	1143	332	-72	1738																			365	125		
	H7	17.5		2093	2128	987	1353	437	-124	1948																			365	125		
	H8	20		2253	2288	1067	1513	517	-163	2108																			365	125		
	H9	23.5		2503	2538	1192	1763	642	-227	2358																			365	125		
MT740	H4	8.5	16000	1453	1488	667	713	117	36	1408	354	695	100	540	340	274	35	150...	978	369	373	300...	185...	90	266	1905	22.5	250				
	H5	11.5		1668	1703	775	928	224	-18	1623																			200	160		
	H6	14.5		1883	1918	882	1143	332	-72	1838																			200	160		
	H7	17.5		2093	2128	987	1353	437	-124	2048																			200	160		
	H8	20		2253	2288	1067	1513	517	-163	2208																			200	160		
	H9	23.5		2503	2538	1192	1763	642	-227	2458																			200	160		

Type	Reeving 4/1		Lifting capacity, kg	Lifting speed m/min			
	Lifting height, m			4	6	4/1	6/1
				Weight, kg			
MT305	H3	6.5	2000	220	242		
	H4	10		232	254		
	H5	13.5		245	267		
MT410	H3	6	4000	425	448		
	H4	10		460	503		
	H5	13		480	523		
MT516	H3	6	6300	465	475	525	
	H4	9		500	510	565	
	H5	12.5		520	530	585	
MT625	H3	5.5	10000	830	890		
	H4	8.5		885	945		
	H5	11.5		940	1000		
	H6	15		1010	1070		
	H7	17.5		1200	1260		
	H8	20		1245	1305		
MT740	H4	8.5	16000	1330	1390		
	H5	11.5		1385	1445		
	H6	14.5		1435	1495		
	H7	17.5		1495	1555		
	H8	20		1540	1600		
	H9	23.5		1610	1670		
	H10	26		1665	1725		
MT750	H4	8.5	20000	1370	1430		
	H5	11.5		1430	1490		
	H6	14.5		1480	1540		
	H7	17.5		1545	1605		
	H8	20		1590	1650		
	H9	23.5		1665	1725		
	H10	26		1725	1785		