



Electric wire rope hoists T01 Stationary one standing (hanging) on clutches, reeving 2/1

- (1) with micro-lifting
- (2) with load limitation
- (3) with load limitation and with micro-lifting

Type	Reeving 2/1		Dimensions, mm																					
	Lifting height, m	Lifting capacity, kg	Lifting speed m/min				L2	L3	L4	L5	L6	L7	H1	H2	H3	B1	B2	B3	B4	B5	e	C	d1	
			8	12	8/2	12/2																		
T012...	H1	6	500	648	688	287	320	37	45	46	70	310	157	17	465	300	200	34	-	18	510	21		
	H2	9		738	778	332	410	60	68														492 ⁽¹⁾	365 ⁽²⁾
	H3	12		818	858	373	490	80	88														557 ⁽³⁾	
	H4	18		978	1018	452	650	55	192															
	H5	24		1138	1178	532	810	55	272															
	H6	30		1226	1290	567	804	89	214														580	380
	H7	36		1306	1373	602	874	110	228														606 ⁽¹⁾	442 ⁽²⁾
T013...	H1	6	1000	709	749	310	365	48	55	46	70	310	157	17	465	300	200	40	-	18	575	21		
	H2	9		814	854	362	470	75	82														492 ⁽¹⁾	365 ⁽²⁾
	H3	12		914	954	412	570	100	106														557 ⁽³⁾	
	H4	18		1114	1154	512	770	75	231															
	H5	24		1314	1354	612	970	149	332															
	H6	30		1426	1490	667	1004	90	312														675	430
	H7	36		1526	1593	712	1094	110	338														682 ⁽¹⁾	508 ⁽²⁾
T014...	H1	6	2000	816	880	362	394	45	51	55	80	402	202	22	580	380	270	45	-	22	665	26		
	H2	9		926	990	417	504	73	79														606 ⁽¹⁾	442 ⁽²⁾
	H3	12		1026	1090	467	604	96	104														668 ⁽³⁾	
	H4	18		1226	1290	567	804	90	212															
	H5	24		1426	1490	667	1004	90	312															
	H6	30		1535	1623	710	1070	88	346														675	430
	H7	36		1640	1728	762	1175	75	398														682 ⁽¹⁾	508 ⁽²⁾

Type	Reeving 2/1		Dimensions, mm																			
	Lifting height, m	Lifting capacity, kg	Lifting speed m/min		L2	L3	L4	L5	L6	L7	H1	H2	H3	B1	B2	B3	B4	B5	e	C	d1	
			16	16/2.5																		
			L1																			
T012...	H4	18	500	1026	1090	467	604	97	106	55	80	402	202	22	580	380	270	34	-	22	510	26
	H5	24		1086	1153	492	654	97	131						606 ⁽¹⁾							
	H6	30		1226	1290	567	804	89	214						668 ⁽³⁾							
	H7	35		1306	1373	602	874	110	228						442 ⁽²⁾							
T013...	H4	18	1000	1086	1153	492	654	110	118	55	80	402	202	22	675	430	270	40	-	22	575	26
	H5	24		1226	1290	567	804	90	212						682 ⁽¹⁾							
	H6	30		1426	1490	667	1004	90	312						760 ⁽³⁾							
	H7	36		1526	1590	712	1094	110	338						508 ⁽²⁾							
T014...	H5	24	2000	1325	1413	605	860	75	242	63	90	497	252	30	675	430	330	45	-	26	665	30
	H6	30		1535	1623	710	1070	88	346						682 ⁽¹⁾							
	H7	36		1640	1728	762	1175	75	398						760 ⁽³⁾							
T015...	H4	18	3200	1325	1413	605	860	75	242	63	90	497	252	26	675	430	330	50	-	26	750	30
	H5	24		1535	1623	710	1070	75	347						682 ⁽¹⁾							
	H6	30		1640	1728	762	1175	75	398						760 ⁽³⁾							
	H7	36		1815	1903	850	1350	75	436						508 ⁽²⁾							
T016...	H4	18	5000	1488	1494	667	958	94	230	84	100	585	300	32	765	470	460	56	82	38	840	28
	H5	24		1588	1594	717	1058	94	280						845 ⁽³⁾							
	H6	30		1778	1784	812	1248	94	330						550 ⁽²⁾							
	H7	36		1963	1969	905	1433	99	462						460							
T017...	H2	9	8000	1168	1174	507	638	77	82	84	100	585	300	32	765	470	460	56	82	38	840	28
	H3	12		1328	1334	587	798	118	123						845 ⁽³⁾							
	H4	18		1488	1494	667	958	78	242						550 ⁽²⁾							
	H5	24		1703	1709	775	1173	78	350						460							
	H6	30		1918	1924	882	1388	78	457						460							
	H7	36		2128	2134	987	1598	78	562						460							

Type	Reeving 2/1		Lifting speed m/min					
	Lifting height, m	Lifting capacity, kg	8	12	8/2	12/2	16	16/2.5
			Weight, kg					
T012...	H1	6	95		113		-	-
	H2	9	100		118		-	-
	H3	12	105		123		-	-
	H4	18	119		137		226	272
	H5	24	128		146		244	290
	H6	30	250		297		251	297
	H7	36	273		320		274	320
T013...	H1	6	107		130		-	-
	H2	9	115		138		-	-
	H3	12	124		147		-	-
	H4	18	137		160		247	293
	H5	24	149		172		263	309
	H6	30	286		333		287	333
	H7	36	306		353		307	353
T014...	H1	6	207		253		-	-
	H2	9	222		268		-	-
	H3	12	232		278		-	-
	H4	18	267		313		-	-
	H5	24	292		338		486	541
	H6	30	526		581		526	581
	H7	36	546		601		546	601
T015...	H1	6	240	250	305		-	-
	H2	9	255	265	320		-	-
	H3	12	270	280	335		-	-
	H4	18	310	320	375		490	545
	H5	24	340	350	405		535	590
	H6	30	525	565	620		565	620
	H7	36	550	590	645		590	645
T016...	H1	6	360		455		-	-
	H2	9	380		475		-	-
	H3	12	400		495		-	-
	H4	18	460		555		818	823
	H5	24	510		605		838	843
	H6	30	570		665		860	865
	H7	36	840		900		900	905
T017...	H2	9	660		720		720	725
	H3	12	700		760		760	765
	H4	18	765		825		825	830
	H5	24	825		885		885	890
	H6	30	880		940		940	945
	H7	36	940		1000		1000	1005